



TKE 335 R
Single head trimming machine

Detail of adjustable stop 01

Graduated scale 02



02

Single head rising blade trimming machine, for extruded profiles and flat sheets made of aluminium. The especially rugged structure allows very sharp and accurate cutting in order to obtain exactly parallel faces of the profiles. Furthermore the machine can be set-up with support roller conveyors to extend its versatility. The blade guard has been designed and developed to ensure working under the best possible conditions of safety.

Cutting zone 03



The images are only given for illustrative purposes

TKE 335 R

Single head trimming machine

01

Detail of adjustable stop

This stop is referred to the blade centerline and allows rapid definition of area of metal removal.

02

Graduated scale

The graduated scale allows mechanical setting of the height of the blade from the horizontal work table in relation to the material to be trimmed.

03

Cutting zone

The rugged and generous cast iron horizontal work table provides a considerable support surface in order to allow trimming both profiles and flat sheets made of aluminium.

BLADE

Carbide-tipped blade dia. (mm)

350

BLADE FEED

Max. trimming height (mm)

120

CUTTING ZONE GUARDS

Local, with manual adjustment

LUBRICATION SYSTEM

Spray-mist lubrication with water and oil emulsion

MOTOR

Three-phase brake motor, operating time 10 sec. (kW)

1,5