

ZS 135/N, ZS 170/N, ZS 200/N

Radial arm saws



ZS 170/N



ZS 200/N

Our know-how - your advantage

Cutting and mitre saw, universally applicable, precise, sturdy, long service life

ZS 135, ZS 135/N, ZS 170, ZS 170/N, ZS 200, ZS 200/N

- suitable for PVC, aluminium and wood
- manual operation of saw head
- saw blade diameter 350 - 520 mm
- cutting height 135 - 200 mm
- 45° right and 45° left, swivelling
- readjustable fixed stops at 90° and 45°
- quick mitre adjustment on clearly legible scale
- solid grey cast iron design
- matured and proven technique

Options

- machine stand
- pneumatic clamping cylinder, vertical
- digital angle display
- hydraulic feed brake
- saw blade spraying device
- version N, inclinable on one side via handwheel



Technical information

	ZS 135	ZS 170	ZS 200
	230/400 V 50-60 Hz L1-L2-L3-N-PE 2 kw	230/400 V 50-60 Hz L1-L2-L3-N-PE 2 kw	230/400 V 50-60 Hz L1-L2-L3-N-PE 5 kw
	100 kgs	105 kgs	300 kgs
		B = 700 mm T = 1200 mm H = 1500 mm	
	3800 U/min	3500 U/min	2800 U/min

	ZS 135	ZS 170	ZS 200
	90° - 20°	90° - 20°	60° - 90° - 30°
	45° - 90° - 45°	45° - 90° - 45°	45° - 90° - 25°
	h = 135 mm l = 430 mm Ø = 350 mm	h = 170 mm l = 410 mm Ø = 420 mm	h = 200 mm l = 420 mm Ø = 520 mm

Technical data are valid for basic machine without options. Size according to layout.

Urban GmbH & Co. Maschinenbau KG

Dornierstraße 5
DE - 87700 Memmingen
Tel.: +49 (0) 8331 858 - 0
E-Mail: urban@u-r-b-a-n.com
www.u-r-b-a-n.com

Subject to errors and modifications