



TECHNICAL SHEET

05/05/2025



Single head rising blade trimming machine, for extruded profiles and flat sheets made of aluminium. The especially rugged structure allows very sharp and accurate cutting in order to obtain exactly parallel faces of the profiles. Furthermore the machine can be set-up with support roller conveyors to extend its versatility. The blade guard has been designed and developed to ensure working under the best possible conditions of safety.



TECHNICAL SHEET

05/05/2025



Adjustable stop

Referring to the centreline of the blade, it allows the area to be removed to be quickly defined.



Graduated scale

It allows the height of the blade relative to the horizontal support surface to be mechanically fixed in relation to the thickness of the material to be sectioned.



Cutting zone

The sturdy and wide horizontal castiron support surface makes up the work area, which features a large footprint that enables the processing of both profiles and flat aluminium sheets.









TKE 335 R / SINGLE HEAD CUTTING-OFF MACHINES

BLADE Made of Widia (mm) Ø = 350

CUTTING AREA PROTECTION

Maximum trimming height (mm)

Local, manually adjusted

120

LUBRICATION SYSTEM

Micro-mist lubrication system with water and oil emulsion

•

MOTOR

Three-phase brakemotor

Brake intervention time (s)

Power (kW)

10

Included • Available O

Emmegi S.p.A. Via delle Industrie, 2 20044 - Arese (MI) ITALY

Tel 39 02356961 P.IVA 01978870366 info@tekna.it www.tekna.it The right to make technical alterations is